according to Regulation (EC) No. 1907/2006 (REACH)

## 50 008 - Dammar varnish, glossy

50008 16.05.23 Article No. **Issue date:** 6.2 (16.05.23) 1/9 Version Page

## SECTION 1: Identification of the substance/mixture and of the

## company/undertaking

## 1.1 Product identifier

50 008 - Dammar varnish, glossy **Trade name** 

**REACH** registration No.

UFI: 7EGF-14J2-800S-JHD7 UFI

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**General use** 

Products for creation of art.

Uses advised against

### 1.3 Details of the supplier of the safety data sheet

H. Schmincke & Co. GmbH & Co. KG

Otto-Hahn-Strasse 2 D-40699 Erkrath

Tel +49 (0) 211 - 2509 - 0 Fax +49 (0) 211 - 2509 - 479

info@schmincke.de www.schmincke.de Schmincke-lab:

mo-th 8.00-16.30, fr 8.00-13.30 tel. +49 (0) 211-2509-474 sdb@schmincke.de

#### 1.4 Emergency telephone number

**Emergencycall Berlin** +49 30-30686700

(24/7 counseling in german and english)

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

## Classification according to EC regulation 1272/2008 (CLP)

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Flam. Liq. 3; H226 Flammable liquid and vapour. STOT SE 3; H335 May cause respiratory irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

## Labelling









Signal word Danger

**Hazard statements** 

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 008 - Dammar varnish, glossy

 Article No.
 50008
 Issue date:
 16.05.23

 Version
 6.2
 ( 16.05.23 )
 Page
 2/ 9

H411 Toxic to aquatic life with long lasting effects.

**Safety precautions** 

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapours.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/.. P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/or shower.

Text for labelling (CLP)

Repeated exposure may cause skin dryness or cracking. (EUH066)

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

#### **Chemical characterisation**

White spirit Dammar resin

CAS-Number --EINECS / ELINCS / NLP --EU index number --REACH registration No. --Hazchem-Code --CI-Number ---

## 3.2 Mixtures

#### Substance 1

solvent naphtha (petroleum), light, aromatic: 60 - 70%

CAS: 64742-95-6

REACH: 01-2119455851-35

Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / -; EUH066 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3;

H336

#### **Additional information**

---

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### **General information**

If you feel unwell, seek medical advice (show the label where possible).

#### In case of inhalation

Provide fresh air.

Seek medical attention if problems persist.

#### In case of skin contact

Thoroughly wash skin with soap and water. Seek medical attention if irritation persists.

After eye contact

according to Regulation (EC) No. 1907/2006 (REACH

## 50 008 - Dammar varnish, glossy

 Article No.
 50008
 Issue date:
 16.05.23

 Version
 6.2
 ( 16.05.23 )
 Page
 3/ 9

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Seek medical attention if irritation persists.

#### After swallowing

Rinse mouth with water. Let water be drunken in little sips (dilution effect).

If you feel unwell, seek medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

--

## 4.3 Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration!

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons

strong water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

### 5.3 Advice for firefighters

### Special protective equipment for firefighters

Use appropriate respiratory protection.

**Additional information** 

---

## **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing.

## 6.2 environmental precautions

Discharge into the environment must be avoided.

## 6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Collect spilled material using paper towels and dispose.

**Additional information** 

---

#### **6.4 Reference to other sections**

Dispose of waste according to applicable legislation.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

### Advices on safe handling

Handle in accordance with good industrial hygiene and safety practice.

### Precautions against fire and explosion

No special measures are required.

---

## 7.2 Conditions for safe storage, including any incompatibilities

#### **Requirements for storerooms and containers**

Keep container tightly closed.

Hints on joint storage

--

Storage class

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 008 - Dammar varnish, glossy

Article No. 50008 Issue date: 16.05.23
Version 6.2 (16.05.23) Page 4/9

---

#### **Further details**

Protect from frost and exposure to sun.

## 7.3 Specific end use(s)

No special measures necessary if stored and handled as prescribed.

## **SECTION 8: Exposure controls/personal protection**

#### **8.1 Control parameters**

94742-95-6 solvent naphtha (petroleum), light, aromatic

_					
	DEU	WEL	50,000	mg/m³	2(II); AGS

#### **DNEL overview**

94742-95-6 solvent naphtha (petroleum), light, aromatic

	// J -/		
DNEL worker	Long-term - inhalation, systemic effects	150,00000	mg/m³
DNEL worker	Long-term - dermal, local effects	25,00000	mg/kg bw/day
DNEL Consumer	Long-term - oral, systemic effects	11,00000	mg/kg bw/day
DNEL Consumer	Long-term - inhalation, systemic effects	32,00000	mg/m³
DNEL Consumer	Long-term - dermal, systemic effects	11,00000	mg/kg bw/day

#### 8.2 Exposure controls

---

#### Occupational exposure controls

#### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection must be worn whenever the WEL levels have been exceeded.

Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

#### **Hand protection**

Qualified materials: Nitrile rubber Layer thickness > 0,35 mm Breakthrough time > 480 min

Ultranitril 492 - MAPA GmbH, Industriestraße 21- 25, D-27404 Zeven, Internet: www.mapa-pro.de

All information was derived in accordance with EU directive 89/686/EWG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves. This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided.

### Eye protection

Goggles

#### Body protection

Wear suitable protective clothing. Wash contaminated clothing prior to re-use.

#### General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling.

## **SECTION 9: Physical and chemical properties**

#### 9.1 information on basic physical and chemical properties

Form liquid

Colouryellowish, clearOdourweak aromatic

	min	max	
Melting point/freezing point			
Initial boiling point and			
boiling range			
Flammability			
Explosion limits			

## 50 008 - Dammar varnish, glossy

Article No.	50008				Issue date:	16.05.23
Version	6.2	( 16.05.23 )			Page	5/ 9
Flash point/flash	point range	34 °C	34 °C			
Ignition tempera	ture					
PH						
Viscosity		8 mm²/s	9 mm <sup>2</sup> /s	40 °C		
Solubility						
Partition coefficie	ent:					
n-octanol/water						
Vapour pressure						
Density and/or re	elative		0,87 g/ml	20 °C		
density						
Relative vapour d	lensity					
Auto-ignition ten	nperature					
Refraction index						

**Danger of explosion** 

9.2 Other information

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Product is stable under normal storage conditions.

## 10.2 Chemical stability

Product is stable under normal storage conditions.

#### 10.3 Possibility of hazardous reactions

## 10.4 Conditions to avoid

Protect from frost and exposure to sun.

## 10.5 Incompatible materials

strong oxidizing agents

## 10.6 Hazardous decomposition products

Hazardous vapours may form during fires.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Toxicological tests**

94742-95-6

solvent naphtha (petroleum), light, aromatic

oral	LD50	Rat	>	3500,00000	mg/kg	-
dermal	LD50	Rat	>	3000,00000	mg/kg	-

Toxicokinetics, metabolism and distribution

**Acute toxicity** 

No data available

In case of inhalation

No data available

After swallowing

No data available

In case of skin contact No data available

After eye contact

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 008 - Dammar varnish, glossy

 Article No.
 50008
 Issue date:
 16.05.23

 Version
 6.2
 ( 16.05.23 )
 Page
 6/ 9

No data available

**Practical experience** 

---

**General remarks** 

---

11.2 Information on other hazards

---

---

## **SECTION 12: Ecological information**

## 12.1 Toxicity

#### **Ecotoxicological effects**

94742-95-6

solvent naphtha (petroleum), light, aromatic

LC50	fish		9,00000	mg/L	(96h)
EC50	Algae	>	2,60000	mg/L	(72h)
EC50	Daphnia magna (Big water		3,20000	mg/L	(48h)

### **Aquatic toxicity**

No data available

Water Hazard Class non hazardous to water

WGK catalog number -

**General information** 

---

## 12.2 Persistence and degradability

**Further details** 

Product is partially biodegradable.

Oxygen demand

---

## 12.3 Bioaccumulative potential

**Bioconcentration factor (BCF)** 

--

Partition coefficient: n-octanol/water

\_\_\_

#### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

No data available

#### 12.6 Endocrine disrupting properties

---

### 12.7 Other adverse effects

---

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 008 - Dammar varnish, glossy

 Article No.
 50008
 Issue date:
 16.05.23

 Version
 6.2
 ( 16.05.23 )
 Page
 7/ 9

**Product** 

Waste key number

080111 Waste paint and varnish containing organic solvents or other dangerous substances

\_\_\_

Recommendation

---

**Package** 

Waste key number

---

Recommendation

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

#### **Additional information**

---

## **SECTION 14: Transport information**

## 14.1 UN number or ID number

1263

#### 14.2 UN proper shipping name

ADR, ADN Paint related material

IMDG, IATA PAINT RELATED MATERIAL

#### 14.3 Transport hazard class(es)

ADR, ADN 3 IMDG 3 IATA 3

## 14.4 Packing group

Ш

### 14.5 Environmental hazards

Marine Pollutant - IMDG Yes
Marine Pollutant - ADN ---

## 14.6 Special precautions for user

## Land transport (ADR/RID)

Code: ADR/RIDF1Kemmler-number30Hazard label ADR3Limited quantities5L

Package: Instructions P001 - IBC03 - LP01 - R001

Package: Special Provisions PP1
Special provisions for packing together MP19
Portable tanks: Instructions T2
Portable tanks: Special Provisions TP1 - TP29
Tank coding LGBF
Tunnel restriction D/E
Remarks --EQ E1

**Special Provisions** 163 - 367 - 650

## Sea transport (IMDG)

**EmS** F-E, S-E

**Special Provisions** 163 - 223 - 367 - 955

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 008 - Dammar varnish, glossy

 Article No.
 50008
 Issue date:
 16.05.23

 Version
 6.2
 ( 16.05.23 )
 Page
 8/ 9

Limited quantities 5L

Package: Instructions P001 - LP01
Package: Special Provisions PP1
IBC: Instructions IBC03
IBC: Provisions -

Tank instructions IMO - Tank instructions UN T2

Tank instructions Special ProvisionsTP1 - TP29Stowage and segregationcategory A

Properties and observations --Remarks --EQ E1

### **Air transport (IATA-DGR)**

 Hazard
 Flammable Liquid

 Passenger
 355 (60L)

 Passenger LQ
 Y344 (10L)

 Cargo
 366 (220L)

 ERG
 3L

 Remarks
 -- 

 EQ
 E1

 Special Provisioning
 A192

### 14.7 Maritime transport in bulk according to IMO instruments

No data available

## **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

## **National regulations**

#### **Europe**

Contents of VOC [%] --Contents of VOC ---

[g/L]

Further regulations, limitations and legal requirements

---

#### **Germany**

Storage class ---

Water Hazard Class non hazardous to water

WGK catalog number --Incident regulation
Information on working limitations

---

Further regulations, limitations and legal requirements

---

### **Switzerland**

Contents of VOC [%]

65 - 68 %

Further regulations, limitations and legal requirements

---

#### **USA**

Further regulations, limitations and legal requirements

---

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 008 - Dammar varnish, glossy

 Article No.
 50008
 Issue date:
 16.05.23

 Version
 6.2
 ( 16.05.23 )
 Page
 9/ 9

**Federal Regulations** 

---

**State Regulations** 

**Canada** 

Further regulations, limitations and legal requirements

--

### 15.2 Chemical Safety Assessment

---

## **SECTION 16: Other information**

#### **Further information**

Hazard statements (CLP) H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### **Further information**

This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

#### Literature

REGULATION (EU) 2021/849 - ATP 17

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

#### Reason of change

--

#### **Additional information**

---

Uppgifterna i detta datablad är sammanställda efter våra bästa kunskaper och motsvarar kända fakta vid datum för omarbetning.

De garanterar dock inte bestämda egenskapers innehåll i rättsligt sammanhang.