

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.	50008	Issue date:	14.12.20
Version	6.1 (10.12.20)	Page	1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name 50 008 - Dammar varnish, glossy
Name INCI
Name Ph. Eur.
REACH registration No.
UFI UFI: 7EGF-14J2-800S-JHD7

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use

Products for creation of art.

Uses advised against

1.3 Details of the supplier of the safety data sheet

H. Schmincke & Co. GmbH & Co. KG
Otto-Hahn-Strasse 2
D-40699 Erkrath
Tel +49 (0) 211 - 2509 - 0
Fax +49 (0) 211 - 2509 - 479
info@schmincke.de
www.schmincke.de
Schmincke-lab:
mo-th 8.00-16.30, fr 8.00-13.30
tel. +49 (0) 211-2509-474
labor@schmincke.de

1.4 Emergency telephone number

**Emergency
Information**

**Emergencycall Berlin
+49 30-30686700
(24/7 counseling in german and english)**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects.
Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.
Flam. Liq. 3; H226 Flammable liquid and vapour.
STOT SE 3; H335 May cause respiratory irritation.
STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling



Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.	50008	Issue date:	14.12.20
Version	6.1 (10.12.20)	Page	2 / 9

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Safety precautions

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P273 Avoid release to the environment.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/..
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower.

Hazard components for labelling

Text for labelling (CLP)

Repeated exposure may cause skin dryness or cracking. (EUH066)

2.3 Other hazards

SECTION 3: Composition / information on ingredients

3.1 Substances

Chemical characterisation

White spirit
Dammar resin
CAS-Number
EINECS / ELINCS / NLP
EU index number
Customs tariff number
REACH registration No.
RTECS-no.
Hazchem-Code
CI-Number

3.2 Mixtures

Substance 1

solvent naphtha (petroleum), light, aromatic: 60 - 70%
CAS: 64742-95-6
REACH: 01-2119455851-35
Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / -; EUH066
/ Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3;
H336

Additional information

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If you feel unwell, seek medical advice (show the label where possible).

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.	50008	Issue date:	14.12.20
Version	6.1 (10.12.20)	Page	3 / 9

In case of inhalation

Provide fresh air. Seek medical attention if problems persist.

In case of skin contact

Remove residues with soap and water. In case of skin irritation, consult a physician.

After eye contact

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 10 - 15 minutes. Seek medical attention if irritation persists.

After swallowing

Rinse mouth with water. Seek medical treatment in case of troubles.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration!

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons

strong water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters

Use appropriate respiratory protection.

Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing.

6.2 environmental precautions

Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Collect spilled material using paper towels and dispose.

Additional information

6.4 Reference to other sections

Dispose of waste according to applicable legislation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Precautions against fire and explosion

No special measures are required.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers

Hints on joint storage

Storage class

Further details

Protect from frost and exposure to sun.

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No. 50008
Version 6.1 (10.12.20)

Issue date: 14.12.20
Page 4 / 9

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

64742-95-6 solvent naphtha (petroleum), light, aromatic

DEU	WEL	50,000	mg/m ³	2(II); AGS
-----	-----	--------	-------------------	------------

DNEL overview

64742-95-6 solvent naphtha (petroleum), light, aromatic

DNEL worker	Long-term - inhalation, system	150,00000	mg/m ³
DNEL worker	Long-term - dermal, local effe	25,00000	mg/kg bw/day
DNEL Consumer	Long-term - oral, systemic eff	11,00000	mg/kg bw/day
DNEL Consumer	Long-term - inhalation, system	32,00000	mg/m ³
DNEL Consumer	Long-term - dermal, systemic e	11,00000	mg/kg bw/day

8.2 Exposure controls

Occupational exposure controls

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.
Respiratory protection must be worn whenever the WEL levels have been exceeded.
Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

Hand protection

Qualified materials: Nitrile rubber
Layer thickness > 0,35 mm
Breakthrough time > 480 min
Ultranitril 492 - MAPA GmbH, Industriestraße 21- 25, D-27404 Zeven, Internet: www.mapa-pro.de
All information was derived in accordance with EU directive 89/686/EWG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves. This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided.

Eye protection

Goggles

Body protection

Wear suitable protective clothing. Wash contaminated clothing prior to re-use.

General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling.

SECTION 9: Physical and chemical properties

9.1 information on basic physical and chemical properties

Form liquid
Colour yellowish, clear
Odour weak aromatic

	min	max
Initial boiling point and boiling range		
Melting point/freezing point		
Flash point/flash point range	34 °C	34 °C
Flammability		
Ignition temperature		
Auto-ignition temperature		
Explosion limits		
Refraction index		

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.	50008	Issue date:	14.12.20
Version	6.1 (10.12.20)	Page	5 / 9

PH
Viscosity
Viscosity 8 mm²/s 9 mm²/s 40 °C

Vapour pressure
Density 0,87 g/ml 20 °C
Partition coefficient: n-octanol/water

Danger of explosion

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

Product is stable under normal storage conditions.

10.2 Chemical stability

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Protect from frost and exposure to sun.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous vapours may form during fires.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological tests

64742-95-6 solvent naphtha (petroleum), light, aromatic

oral	LD50	Rat	>	2000,00000	mg/kg	-
inhalative	LC50	Rat	>	10,20000	mg/L	(4h)
dermal	LD50	Rat	>	2000,00000	mg/kg	-

Acute toxicity

No data available

In case of inhalation

No data available

After swallowing

No data available

In case of skin contact

No data available

After eye contact

No data available

Practical experience

General remarks

SECTION 12: Ecological information

12.1 Toxicity

Ecotoxicological effects

64742-95-6 solvent naphtha (petroleum), light, aromatic

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.	50008	Issue date:	14.12.20
Version	6.1 (10.12.20)	Page	6 / 9

LC50	fish		9,20000	mg/L	(96h)
EC50	Algae	>	2,60000	mg/L	(72h)
EC50	Daphnia magna (Big water flea)		3,20000	mg/L	(48h)

Aquatic toxicity

No data available

Water Hazard Class

non hazardous to water

WGK catalog number

General information

12.2 Persistence and degradability

Further details

Product is partially biodegradable.

Oxygen demand

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)

Partition coefficient: n-octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number

080111 Waste paint and varnish containing organic solvents or other dangerous substances

Recommendation

Contaminated packaging

Waste key number

Recommendation

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

Additional information

SECTION 14: Transport information

14.1 UN number

1263

14.2 UN proper shipping name

ADR, ADN

Paint related material

IMDG, IATA

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR, ADN

3

IMDG

3

IATA

3

14.4 Packing group

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.	50008	Issue date:	14.12.20
Version	6.1 (10.12.20)	Page	7 / 9

III

14.5 Environmental hazards

Marine Pollutant - IMDG	Yes
Marine Pollutant - ADN	

14.6 Special precautions for user

Land transport (ADR/RID)

Code: ADR/RID	F1
Kemmler-number	30
Hazard label ADR	3
Limited quantities	5L
Contaminated packaging: Instructions	P001 - IBC03 - LP01 - R001
Contaminated packaging: Special provisions	PP1
Special provisions for packing together	MP19
Portable tanks: Instructions	T2
Portable tanks: Special provisions	TP1 - TP29
Tank coding	LGBF
Tunnel restriction	D/E
Remarks	
EQ	E1
Special provisions	163 - 367 - 650

Sea transport (IMDG)

EmS	F-E, S-E
Special provisions	163 - 223 - 367 - 955
Limited quantities	5L
Contaminated packaging: Instructions	P001 - LP01
Contaminated packaging: Special provisions	PP1
IBC: Instructions	IBC03
IBC: Provisions	-
Tank instructions IMO	-
Tank instructions UN	T2
Tank instructions Special provisions	TP1 - TP29
Stowage and segregation	category A
Properties and observations	
Remarks	
EQ	E1

Air transport (IATA-DGR)

Hazard	Flammable Liquid
Passenger	355 (60L)
Passenger LQ	Y344 (10L)
Cargo	366 (220L)
ERG	3L
Remarks	
EQ	E1
Special Provisioning	A192

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

Bezeichner in aktueller Sprache fehlt!

National regulations

Europe

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.	50008	Issue date:	14.12.20
Version	6.1 (10.12.20)	Page	8 / 9

Contents of VOC [%]

Contents of VOC

[g/L]

Further regulations, limitations and legal requirements

Germany

Storage class

Water Hazard Class non hazardous to water

WGK catalog number

Incident regulation

Information on working limitations

Further regulations, limitations and legal requirements

Denmark

Further regulations, limitations and legal requirements

Hungary

Further regulations, limitations and legal requirements

Great Britain

Further regulations, limitations and legal requirements

Switzerland

Contents of VOC [%]

65 - 68 %

Further regulations, limitations and legal requirements

USA

Signal Word

DANGER !

Principal Hazards

Flammable. Harmful or fatal if swallowed.

Hazardous Ingredients

Contains petroleum distillates.

Hazard Statement

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Causes eye, skin, nose and throat irritation.

Precaution Statement

Keep away from heat sparks and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Pregnant women should avoid exposure to solvents.

First aid Statements

If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, immediately flush eyes with plenty of water for 15 minutes and get medical attention immediately. For skin, wash thoroughly with soap and water.

Children's Statement

Keep out of reach of children.

Required Statements

Conforms to ASTM D-4236. For additional health information call the Poison Control Center 1-800-222-1222.

Canada

Further regulations, limitations and legal requirements

15.2 Chemical Safety Assessment

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

50 008 - Dammar varnish, glossy

Article No.	50008	Issue date:	14.12.20
Version	6.1 (10.12.20)	Page	9/ 9

SECTION 16: Other information

Further information

Hazard statements (CLP)	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
--------------------------------	---

Further information

This information is based on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

Literature

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Reason of change

Additional information