50 404 - Fixative B72

Article No.	50404		Issue date:	26.02.24
Version	1	(26.02.24)	Page	1/ 11
	SECTION	1.1. Identification of the su	bstance/mixture and of the	
		company/unde	rtaking	
1.1 Product ide				
Trade name		04 - Fixative B72		
REACH registrati UFI		Q6XO-MFGQ-G102-1HCP		
•••				
1.2 Relevant id	entified uses of tl	<u>he substance or mixture and uses ac</u>	<u>lvised against</u>	
Genera		the opticitie design of land heaving and a	alid substrates	
	Products for	the artistic design of load-bearing and se	olid substrates.	
Uses ad	lvised against			
	Applications	other than "General use"		
	H. Schminck Otto-Hahn-S D-40699 Erk Tel +49 (0) Fax +49 (0) info@schmir www.schmir Schmincke-k mo-th 8.00-	rrath 211 - 2509 - 0 211 - 2509 - 479 ncke.de ncke.de ab: 16.30, fr 8.00-13.30 211-2509-474 ncke.de		
4	mergencycall B -49 30-3068670 24/7 counselin			
		SECTION 2: Hazards	identification	

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Eye Irrit. 2; H319 Causes serious eye irritation. Flam. Liq. 2; H225 Highly flammable liquid and vapour. STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling





Signal word

Danger

H225 Highly flammable liquid and vapour.H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

Safety precautions

Hazard statements

P102 Keep out of reach of children.

50 404 - Fixative B72

Article No. Version	50404 1	(26.02.24)	Issue date: Page	26.02.24 2/ 11
	smc P26 P30	oking. 1 Avoid breathing vapours.	ks, open flames and other ignition sources. No y with water for several minutes. Remove contact ing.	
2.3 Other hazards				

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical characterisation acrylic resin Alcohols ketone UV-protection	
CAS-Number EINECS / ELINCS / NLP	
REACH registration No. CI-Number	

3.2 Mixtures

Substance 1
1-methoxy-2-propanol: 25 < 50 %
CAS: 107-98-2
REACH: 01-2119457435-35
Flam. Liq. 3; H226 / STOT SE 3; H336

Substance 3

butanone: 2,5 < 5 % CAS: 78-93-3

Eye Irrit. 2; H319 / Flam. Liq. 2; H225 / STOT SE 3; H336

Substance 5EO bis(benztriazolyl)phenylpropionat:0,1 - 0,5 %CAS: 104810-47-1Aquatic Chronic 2; H411 / Skin Sens. 1A; H317

Substance 2	
ethanol: 25 < 50 %	
CAS: 64-17-5	
REACH: 01-2119457610-43	
Eye Irrit. 2; H319 / Flam. Liq. 2; H225	

Substance 4

acetone: 2 < 3 % CAS: 67-64-1 REACH: 01-2119471330-49

Eye Irrit. 2; H319 / Flam. Liq. 2; H225 / STOT SE 3; H336

Additional information

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If you feel unwell, seek medical advice (show the label where possible).

In case of inhalation

No special measures are required.

In case of skin contact

Thoroughly wash skin with soap and water.

50 404 - Fixative B72

Article No.	50404		Issue date:	26.02.24
Version	1	(26.02.24)	Page	3/ 11

Seek medical attention if irritation persists.

After eye contact

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Seek medical attention if irritation persists.

After swallowing

Rinse mouth with water. Let water be drunken in little sips (dilution effect). If you feel unwell, seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons

strong water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters

Use appropriate respiratory protection.

Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing.

6.2 environmental precautions

Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Collect spilled material using paper towels and dispose.

Additional information

6.4 Reference to other sections

Dispose of waste according to applicable legislation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Precautions against fire and explosion

No special measures are required.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers Keep container tightly closed.

Hints on joint storage

50 404 - Fixative B72

Article No.	50404		Issue date:	26.02.24
Version	1	(26.02.24)	Page	4/ 11

Storage class

---**Further details**

Protect from frost and exposure to sun.

7.3 Specific end use(s)

No special measures necessary if stored and handled as prescribed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL overview 107-98-2

L07-98-2	1-methoxy-2-propanol			
	DNEL worker	Long-term - inhalation, systemic effects	369,00000	mg/m³
	DNEL worker	Long-term - dermal, systemic effects	50,60000	mg/kg
	DNEL worker	Acute - inhalation, local effects	553,50000	mg/m³
	DNEL Consumer	Long-term - oral, systemic effects	33,00000	mg/kg bw/day
	DNEL Consumer	Long-term - inhalation, local effects	43,90000	mg/m³
	DNEL Consumer	Long-term - dermal, systemic effects	78,00000	mg/kg

DNEL overview

64-17-5 ethanol DNEL worker Long-term - inhalation, systemic effects 950,00000 mg/m³ 343,00000 mg/kg DNEL worker Long-term - dermal, systemic effects Long-term - oral, systemic effects 87,00000 DNEL Consumer mg/kg DNEL Consumer Long-term - inhalation, systemic effects 114,00000 mg/m³ DNEL Consumer Long-term - dermal, systemic effects 206,00000 mg/kg

DNEL overview

67-64-1

dectone			
DNEL worker	Long-term - inhalation, systemic effects	1210,00000	mg/m³
DNEL worker	Long-term - dermal, systemic effects	186,00000	mg/kg bw/day
DNEL worker	Acute - inhalation, local effects	2420,00000	mg/m³
DNEL Consumer	Long-term - oral, systemic effects	62,00000	mg/kg bw/day
DNEL Consumer	Long-term - inhalation, systemic effects	200,00000	mg/m³
DNEL Consumer	Long-term - dermal, systemic effects	62,00000	mg/kg bw/day

DNEL overview

EO bis(benztriazolyl)phenylpropionat 104810-47-1

acetone

DNEL worker	Long-term - inhalation, systemic effects	0,35000	mg/m³
DNEL worker	Long-term - dermal, systemic effects	0,50000	mg/kg
DNEL Consumer	Long-term - oral, systemic effects	0,02500	mg/kg
DNEL Consumer	Long-term - inhalation, systemic effects	0,08500	mg/m³
DNEL Consumer	Long-term - dermal, systemic effects	0,25000	mg/kg

PNEC overview 107-98-7

L07-98-2	1-methoxy-2-propar	lol	-
	PNEC soil	4,59000	mg/kg
	PNEC aquatic, freshwater	10,00000	mg/L
	PNEC aquatic, marine water	1,00000	mg/L
	PNEC soil, freshwater	52,30000	mg/kg
	PNEC soil, marine water	5,20000	mg/kg

50 404 - Fixative B72

Article No.	50404		Issue date:	26.02.24
Version	1	(26.02.24)	Page	5/ 11
				-

mg/L

100,00000

PNEC overview

64-17-5 ethanol

PNEC sewage treatment plant (STP)

PNEC soil	0,63000	mg/kg
PNEC aquatic, freshwater	0,96000	mg/L
PNEC aquatic, marine water	0,79000	mg/L
PNEC soil, freshwater	3,60000	mg/kg
PNEC soil, marine water	2,90000	mg/kg
PNEC sewage treatment plant (STP)	580,00000	mg/L

PNEC overview

67-64-1 acetone

PNEC soil	29,50000	mg/kg
PNEC aquatic, freshwater	10,60000	mg/L
PNEC aquatic, marine water	1,06000	mg/L
PNEC soil, freshwater	30,40000	mg/kg
PNEC soil, marine water	3,04000	mg/kg
PNEC sewage treatment plant (STP)	100,00000	mg/L

PNEC overview

104810-47-1

EO bis(benztriazolyl)phenylpropionat

PNEC soil	2,00000	mg/kg
PNEC aquatic, freshwater	0,00230	mg/L
PNEC aquatic, marine water	0,00023	mg/L
PNEC soil, freshwater	3,06000	mg/kg
PNEC soil, marine water	0,30600	mg/kg

8.2 Exposure controls

Occupational exposure controls

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection must be worn whenever the WEL levels have been exceeded. Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

Hand protection

Qualified materials: Nitrile rubber

Layer thickness > 0,35 mm

Breakthrough time > 480 min

Ultranitril 492 - MAPA GmbH, Industriestraße 21-25, D-27404 Zeven, Internet: www.mapa-pro.de All information was derived in accordance with EU directive 89/686/EWG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves. This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided.

Eye protection

Goggles

Body protection

Wear suitable protective clothing. Wash contaminated clothing prior to re-use.

General protection and hygiene measures Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling.

SECTION 9: Physical and chemical properties

9.1 information on basic physical and chemical properties

Form

50 404 - Fixative B72

Article No. Version	50404 1	(26.02.24)			Issue date: Page	26.02.24 6/ 11
Colour	clear					
Odour	weak sweetish					
		min	max			
Melting point/fre	ezing point					
Initial boiling poi	nt and					
boiling range						
Flammability						
Explosion limits						
Flash point/flash	point range	15 °C	15 °C			
Ignition temperat	ture					
PH						
Viscosity						
Viscosity		11 mm²/s	12 mm²/s	40 °C		
Solubility						
Partition coefficie	ent: n-octanol/water					
Vapour pressure						
Density and/or re	elative		0,88 g/ml	20 °C		
density						
Relative vapour d	lensity			-		
Auto-ignition tem	perature					
Refraction index						

Danger of explosion particle characteristics

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

Product is stable under normal storage conditions.

10.2 Chemical stability

Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Protect from frost and exposure to sun.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous vapours may form during fires.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological tests 107-98-2

1-methoxy-2-propanol

oral	LD50	Rat		4016,00000	mg/kg	-
inhalative	LC50	Rat	>	25,80000	mg/L	(6h)

50 404 - Fixative B72

Article No. Version	50404 1	(26.	02.24)			Issue date: Page	26.02.24 7/ 11
[dermal	LD50	Rabbit	>	2000,00000	mg/kg	-
Toxicological tests 64-17-5	s ethanol						
	oral	LD50	Rat		10470,00000	mg/kg	-
	inhalative	LC50	Rat		38,00000	mg/L	(4h)
	inhalative	LC50	Mouse	>	20,00000	mg/L	(4h)
	dermal	LD50	Rabbit	>	2000,00000	mg/kg	-
Toxicological tests 78-93-3	s butano	ne					
[oral	LD50	Rat		2740,00000	mg/kg	-
	dermal	LD50	Rabbit		6480,00000	mg/kg	-
Toxicological tests 67-64-1	acetone	r	1				
	oral	1.050	Dat		5800 00000	ma/ka	-

	oral	LD50	Rat		5800,00000	mg/kg	-
	inhalative	LC50	Rat	>	76,00000	mg/L	(4h)
[dermal	LD50	Rabbit		7400,00000	mg/kg	-

Toxicokinetics, metabolism and

distribution

Acute toxicity

There are no data available on the preparation/mixture itself. In case of inhalation

There are no data available on the preparation/mixture itself. After swallowing

There are no data available on the preparation/mixture itself. In case of skin contact

There are no data available on the preparation/mixture itself. After eye contact

There are no data available on the preparation/mixture itself.

Sensibilisation: Respiratory

system

There are no data available on the preparation/mixture itself. Sensibilisation: Skin

There are no data available on the preparation/mixture itself. **Specific target organ**

toxicity

There are no data available on the preparation/mixture itself. **Repeated dose toxicity**

There are no data available on the preparation/mixture itself.

Carcinogenic, germ cell mutagen and reproduction effects

Practical experience

General remarks

11.2 Information on other hazards

50 404 - Fixative B72

Version 1 (26.02.24) Page 8/11	Article No.	50404		Issue date:	26.02.24
	Version	1	(26.02.24)	Page	

SECTION 12: Ecological information

12.1 Toxicity

Ecotoxicological effects

64-17-5 ethanol

LC50	Leuciscus idus		8140,00000	mg/L	48h
EC50	Chlorella vulgaris		275,00000	mg/L	(72h)
EC50	Daphnia magna	>	10000,00000	mg/L	48h

Ecotoxicological effects

78-93-3 butanone

[LC50	fish	3220,00000	mg/L	(96h)
	EC50	Daphnia magna (Big water	5090,00000	mg/L	(48h)

Ecotoxicological effects

67-64-1 acetone

[LC50	Oncorhynchus mykiss	>	5540,00000	mg/L	(96h)
	EC50	Selenastrum capricornutum	>	7500,00000	mg/L	(96h)
[EC50	Daphnia magna (Big water	>	8800,00000	mg/L	(48h)

Ecotoxicological effects

104810-47-1 EO bis(benztriazolyl)phenylpropionat

LC50	Oncorhynchus mykiss	2,80000	mg/L	(96h)
EC50	Daphnia magna (Big water	4,00000	mg/L	(48h)

Aquatic toxicity

No data availableWater Hazard Class1WGK catalog number---General information---

12.2 Persistence and degradability

Further details

Product is partially biodegradable. **Oxygen demand**

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)

Partition coefficient: n-octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

50 404 - Fixative B72

Article No.	50404		Issue date:	26.02.24
Version	1 ((26.02.24)	Page	9/ 11

12.7 Other adverse effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number

080111 080111* waste paint and varnish containing organic solvents or other dangerous substances

Recommendation

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains.

Package

Waste key number

Recommendation

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

Additional information

https://www.schmincke.de/en/know-how/good-to-know/disposing-of-washing-water-colour-medium-remains

SECTION 14: Transport information

14.1 UN number or ID number

1263

14.2 UN proper shipping name

ADR, ADN	Paint related material
IMDG, IATA	PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR, ADN	3
IMDG	3
ΙΑΤΑ	3

14.4 Packing group

III

14.5 Environmental hazards

No
F1
30
3
5L
P001 - IBC03 - LP01 - R001
PP1
MP19
T2
TP1 - TP29
LGBF

50 404 - Fixative B72

Article No.	50404		Issue date:	26.02.24
Version	1	(26.02.24)	Page	10/ 11
		. ,		
Tunnel restric	tion	D/E		
Remarks				
EQ		E1		
Special Provis	ions	163 - 367 - 650		
<u>Sea transport</u>	(IMDG)			
EmS		F-E, S-E		
Special Provis	ions	163 - 223 - 367 - 955		
Limited quant		5L		
Package: Inst		P001 - LP01		
Package: Spec		PP1		
IBC: Instruction		IBC03		
IBC: Provision	IS	-		
Tank instructi	ons IMO	-		
Tank instructi	ons UN	T2		
Tank instructi	ons Special Provisions	TP1 - TP29		
Stowage and		category A		
Properties and	d observations			
Remarks				
EQ		E1		
<u>Air transport (</u>	(IATA-DGR)			
Hazard		Flammable Liquid		
Passenger		355 (60L)		
Passenger LQ		Y344 (10L)		
Cargo		366 (220L)		
ERG		3L		
Remarks				
EQ		E1		
Special Provis	ioning	A192		

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

<u>Europe</u>

Contents of VOC [%]	89,5
Contents of VOC	
[g/L] Further regulations, limita 	tions and legal requirements

<u>Germany</u>

Storage class	LK 3
Water Hazard Class	1
WGK catalog number	
Incident regulation	
Information on working limitations	

Further regulations, limitations and legal requirements

Switzerland

50 404 - Fixative B72

Article No.	50404		Issue date:	26.02.24
Version	1	(26.02.24)	Page	11/ 11

Contents of VOC [%]

89,5

Further regulations, limitations and legal requirements

<u>USA</u>

Further regulations, limitations and legal requirements

Federal Regulations

State Regulations

<u>Canada</u>

Further regulations, limitations and legal requirements

15.2 Chemical Safety Assessment

SECTION 16: Other information

Further information

Hazard statements (CLP)	H225 Highly flammable liquid and vapour.
	H226 Flammable liquid and vapour.
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Further information

This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

Literature

REGULATION (EU) 2021/849 - ATP 17

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Additional information
