

50 017 mastic varnish, semi-glossy

product name:

- Mastic varnish, semi-glossy.

contains:

- Mastic resin, oil of turpentine.

basic information:

- Final varnish for paintings in oil made from extra light Chios mastic.

characteristics:

- Semi-glossy
- hardly yellowing
- fast drying.

handling:

- Shake well before use.
- The product is ready to use, but can be diluted with *oil of turpentine 50024 / 50102*.
- May only be applied with a suitable varnish brush at room temperature to the layer of oil paint after it has dried completely, i.e. after 8 – 12 month at the earliest.
- Please clean tools as soon as possible with e.g. *oil of turpentine 50024 / 50102* or *brush cleaner 50051 / 50052*.
- The dried varnish layer remains soluble in *oil of turpentine 50024 / 50102* or *varnish remover 50060* over a long period.
- Mastic or products with mastic are not dilutable or resoluble in *turpentine substitute 50019*.
- Varnishes produced with mastic are less flexible and show a higher tendency for yellowing than varnishes produced with dammar.
- The varnish coats normally used in practice give no special UV protection to the paints used. For this reason, we recommend that you use high-quality and lightfast oil paints from the outset as far as possible.
- Close immediately after use.
- Store in a cool and dry place.
- Individual pre-tests are required (see footer).

product labeling:

- Please refer to the individual safety data sheet on our website www.schmincke.de.

DrK/01.07.2014

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·
Tel.: +49-211-2509-0 · www.schmincke.de · info@schmincke.de



The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.