

50 511 size / primer

product name:

- Size / primer.

contains:

- Acrylate styrol dispersion.

basic information:

- Primer for pre-priming and consolidating absorbing and sandy mineral surfaces like plaster or concrete.

characteristics:

- Colorless
- transparent
- elastic
- light-resistant and non-aging.

handling:

- Shake well and stir – if necessary – before use.
- The mineral surfaces should be clean, dry, intact and without any mould-release agents.
- The kind of use depends on the absorbance of the surface being treated.
- *Size / primer* is mixable with water, but dries up to a water-insoluble film.
- Normally one uses the product in dilution with 4 parts water. In the case of difficult surfaces (very absorbent / sandy) please use the concentrate. (It is important that there is no closed film on the surface!)
- The product can be applied with a brush, a paint roller or an airbrush.
- Please clean tools like brushes as soon as possible with water or water and soap.
- Please don't use the product below temperatures under 5 °C object- and room-temperatures. Also beware the application on warm surfaces or under direct sun irritation!
- As primer afterwards we recommend i.e. *Schmincke primer 1, strongly absorbent 50512* or *Schmincke primer 2, 50514*.
- Please take care that for outdoor paints additional arrangements have to be made (e.g. paints with maximum light fastness; sealing with *acrylic lacquer, glossy 50 586* or *acrylic lacquer, satin glossy 50 587*).
- Close immediately after use.
- Store in a cool and dry place.
- Protect from frost.
- Individual pre-tests are required (see footer).

product labeling:

- Please refer to the individual safety data sheet on our website www.schmincke.de.

DrK/ 01.07.2014



H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·
Tel.: +49-211-2509-0 · www.schmincke.de · info@schmincke.de

The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.