

## 50 518 gesso

### product name:

- Gesso.

### contains:

- Copolymer dispersion.

### basic information:

- Primer for oil and acrylic colours with stronger absorbent character similar to a half-chalk ground (gesso) for greaseless surfaces, like e.g. canvas, wood or cardboard in student quality.

### characteristics:

- white
- semi-transparent
- fine
- matt
- elastic
- light-resistant and non-aging

### handling:

- Shake well and stir – if necessary – before use.
- Gesso is ready for use and should be applied in two or three thin layers. (The previous coat has to be completely dry before the next coat is applied!)
- The product can be diluted with max. 10 % of water if necessary.
- It dries up water-insoluble.
- If necessary the product is allowed to be sand down finely.
- If the primer is required in a different colour shade, the product can be individually tinted with using Schmincke acrylic colours.
- If the surface is extremely absorbent like natural canvas, it should be pretreated with *size/pre-primer 50510*.
- Please clean tools like brushes as soon as possible with water or water and soap.
- Please don't use the product below temperatures under 10 °C object- and room-temperatures.
- Close immediately after use.
- Store in a cool and dry place.
- Protect from frost.
- Individual pre-tests are required (see footer).

### product labeling:

- Please refer to the individual safety data sheet on our website [www.schmincke.de](http://www.schmincke.de).

DrK/ 01.07.2014

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·  
Tel.: +49-211-2509-0 · [www.schmincke.de](http://www.schmincke.de) · [info@schmincke.de](mailto:info@schmincke.de)



The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.