

50 530 fibre gel

product name:

- Fibre gel.

contains:

- Pure acrylate dispersion, pigments, additives, water.

basic information:

- Effect gel for acrylic colours for bizarre surface structures.

characteristics:

- smooth consistency
- semi-opaque
- contains fibres.

handling:

- Stir – if necessary – before use.
- *Fibre gel* is ready for use and should be applied pure or mixed with acrylic colours with a pallet knife onto a greaseless painting ground.
- If coats thicker than 1,0 cm are required, these should be built in stages.
- The time for drying depends on the thickness of the surface and can last from several minutes up to several hours.
- Can be overpainted with acrylic colours after getting completely dry.
- The product can be diluted with water, but dries up water-insoluble.
- Please clean tools as soon as possible with water or water and soap. Just dried acrylic colours can be removed with *brush cleaner 50051 / 50052*.
- Please don't use the product below temperatures under 10 °C object- and room-temperatures.
- Close immediately after use.
- Store in a cool and dry place.
- Protect from frost.
- Individual pre-tests are required (see footer).

product labeling:

- Please refer to the individual safety data sheet on our website www.schmincke.de.

DrK/ 01.07.2014

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·
Tel.: +49-211-2509-0 · www.schmincke.de · info@schmincke.de



The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.