

50 555 acrylic binder

product name:

- Acrylic binder.

contains:

- Pure acrylate dispersion.

basic information:

- Binder for own production of acrylic colours, acrylic mediums and primers in combination with Schmincke Pure Artists' Pigments; addition to Schmincke acrylic colours (instead of water) optimized adhesive properties and increases gloss and transparency.

characteristics:

- Colourless
- glossy
- water-mixable
- non-yellowing and age-resistant.

handling:

- Shake well before use.
- *Acrylic binder* is ready to use, but can be diluted with water if necessary.
- The mixing ratio of binder to pigment very much depends on the type of dyestuff. Our recommendation: Start off with the same amount of binder and pigment, than add binder or pigment until the required consistency. The dried streaks of paint should have a smooth surface and do not come off when rubbed with the dry heel of the hand. The self-mixed colours can be diluted with water if necessary. They are intended to be used as quickly as possible and should only be stored for a few days in screw-top jars.
- The product can be mixed with acrylic colours as desired – as possible on a separate palette.
- The product can be diluted with water, but dries up to a water-insoluble film.
- Please clean tools as soon as possible with water or water and soap. Just dried acrylic colours can be removed with *brush cleaner 50051 / 50052*.
- Please don't use the product below temperatures under 10 °C object- and room-temperatures.
- Close immediately after use.
- Store in a cool and dry place.
- Protect from frost.
- Individual pre-tests are required (see footer).

product labeling:

- Please refer to the individual safety data sheet on our website www.schmincke.de

DrK/ 01.07.2014

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·
Tel.: +49-211-2509-0 · www.schmincke.de · info@schmincke.de



The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.