

50 708 AQUA Lift-off-Medium

product name:

- AQUA Lift-off-Medium

contains:

- Water, pure acrylate dispersion, additives

basic information:

- Medium for water-colours to decrease their staining power

characteristics:

- Decreases staining power and improves resolving of dry water-colours from painting-ground

handling:

- Shake well before use.
- AQUA fix is ready to use with lightly sized papers (for example mould-made papers). For use on stronger surface-glued papers (for example student quality) the product should be diluted with water; pre-testing is recommended.
- The product should be used as a size: brush the painting-ground before painting with water-colour and let thoroughly dry.
- The product may never be put directly into the pans.
- The product can be diluted with water, but dries up to a water-insoluble film.
- Please clean tools like brushes as soon as possible with water or water and soap.
- Please don't use the product below temperatures under 10 °C object- and room-temperatures.
- Close immediately after use.
- Store in a cool and dry place.
- Protect from frost.
- Individual pre-tests are required (see footer).

product labeling:

- Please refer to the individual safety data sheet on our website www.schmincke.de.

CM/ 29.11.2016

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·
Tel.: +49-211-2509-0 · www.schmincke.de · info@schmincke.de



The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.