

50 810 oil binder “Ready-to-use“

product name:

- Oil binder “Ready-to-use“.

ingredients:

- Natural vegetable oils, additives.

basic information:

- Ready-to-use binder for easy grinding of pasty oil colours in combination with Schmincke pure artists' pigments.

characteristics:

- Produced with siccatives for a good and thorough drying process
- due to very little yellowing also suitable for pale colours.

handling:

- Shake well before use.
- *Oil binder „Ready-to-use“* is ready to use, but can be diluted with e.g. *turpentine substitute 50019*.
- Grind a teaspoonful of pigment and a small amount of product with a paint knife on a grinding plate made of glass or a flat glazed tile to a smooth paste.
- The mixing ratio of binder to pigment very much depends on the type of pigment. Start off with approx. 1 part binder to 1 part pigment (by weight). Depending on the pigment, more binder or more pigment is added to achieve the required consistency. The right proportions have been reached if dried streaks of paint have a smooth surface and do not come off when rubbed with the dry heel of the hand.
- Please clean tools like brushes or palettes as soon as possible with e.g. *oil of turpentine 50024 / 50102, turpentine substitute 50019 or brush cleaner 50051 / 50052*.
- Close immediately after use.
- Store in a cool and dry place.
- Individual pre-tests are required (see footer).

General hints for working with drying vegetable oils:

- Colours with a binder based on vegetable oils show a tendency for yellowing specially in the dark.
- Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be placed in a close metal container soaked with water or washed out well with warm soapy water before disposal. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

product labeling:

- Please refer to the individual safety data sheet on our website www.schmincke.de.

DrK/01.07.2014

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·
Tel.: +49-211-2509-0 · www.schmincke.de · info@schmincke.de



The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.