

50 840 acrylic binder „ready-to-use“

product name:

- Acrylic binder „ready-to-use“.

contains:

- Pure acrylic dispersion, wetting agent.

basic information:

- Ready-to-use binder for easy grinding of satin-matt acrylic colours in combination with Schmincke pure artists' pigments.

characteristics:

- Dilutable with water, but dries up to a water-insoluble film
- non-yellowing.

handling:

- Shake well before use.
- *Acrylic binder "ready-to-use"* is ready to use, but can be diluted with water if necessary.
- Grind a teaspoonful of pigment and a small amount of product with a paint knife on a grinding plate made of glass or a flat glazed tile to a smooth paste.
- The mixing ratio of binder to pigment very much depends on the type of pigment. Start off with approx. 2 part binder to 1 part pigment (by weight). Depending on the pigment, more binder or more pigment is added to achieve the required consistency. The right proportions have been reached if dried streaks of paint have a smooth surface and do not come off when rubbed with the dry heel of the hand.
- The product is water-mixable, but dries up water-insoluble.
- Please clean tools as soon as possible with water or water and soap. Just dried acrylic colours can be removed with *brush cleaner 50051 / 50052*.
- Please don't use the product below temperatures under 10 °C object- and room-temperatures.
- Close immediately after use.
- Store in a cool and dry place.
- Protect from frost.
- Individual pre-tests are required (see footer).

product labeling:

- Please refer to the individual safety data sheet on our website www.schmincke.de

DrK/ 01.07.2014

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D- 40699 Erkrath ·

Tel.: +49-211-2509-0 · www.schmincke.de · info@schmincke.de

The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.